


FIREPROOF GLAZED STEELPROFILE DOOR E30/E60

2/2014



Area: Internal door
Profile: SP35000
Fire class: E30/E60

DETAILED INFORMATION

Produced from Stålprofil AB steel profile
Steel thickness 1,5 mm
Profile depth 50 mm (door leaf and frame)
Profile with 30 to 85 mm

FINISHING MATERIALS

Ground painted
Stainless steel AISI 316L (brushed or polished finish)
Painted in RAL or NCS color (wet or powder painted)
Special finishing: copper, brass and lacquered steel

SILL TYPES

20 mm stainless steel tube sill as standard
Without sill
Automatic dropdown sill
Other sill options available

GLASS

Glass to be specified according to project and certificate

LOCKS

All well-known online and offline hardware according to specification (ASSA, Abloy etc.)

CLOSING DEVICE

All well-known hardware (Dorma, Geze, Dorint etc.)
Integrated / Concealed closers (Abloy, Dorint etc.)

T-Tammer fire doors are tested according to all applicable specifications and are type-approved by:
VTT - VTT Expert Services Oy
Inspecta - OÜ Inspecta Estonia
SP SITAC, Sweden - Swedish Institute for Technical Approval in Construction
DS- Danish Institute of Fire and Security Technology
TÜV – OÜ TÜV Eesti
For more information about T-Tammer certificates, please ask from our staff.